

# New Hatch Covers have productivity covered

- The first universal hatch cover designed to meet both vented and non-vented
- Self-adjusting latch maintains gasket compression during extreme temperatures
- Rugged ABS construction, lighter weight without compromising strength
- Safeguards material falling into load due to vibration
- Lower profile design eliminates locking arm and requires no tools for in-service adjustment
- Sleek design cuts down on tripping hazard



	Amsted Rail Universal	Competitor Non-Vented	Competitor Vented
<b>Performance Features</b>			
Convertible to Vent or Non-Vented	<b>Yes</b>	No	No
Self-Adjusting Gasket Compression	<b>Yes</b>	No	No
Requires Tools for In-Service Adjustment	<b>No</b>	Yes	Yes
IONX Ready	<b>Yes</b>	No	No
Warranty (years)	5	5	5
<b>Physical Features</b>			
Cover Material	ABS	ABS	HMWPE
UV Protection	Yes	Yes	Yes
Area	576.7 sq. in.	452.4 sq. in.	585.7 sq. in.
Gasket Material	TPE	TPE	TPE
FDA Approved Gasket and Screen	Yes	Yes	Yes
Cover Wall Thickness	0.19	.25-.31	.085-.25
Overall Height (top of arm)	3.75 in.	3.5 in.	4.5 in.
# of Components (including bolts)	14	18	20
Overall Weight	(Non-Vented) 11.5 lbs. (Vented) 10.7lbs	13.4 lbs.	16.6lbs.

A world apart in reliability **Amsted Rail**<sup>®</sup>

**Amsted Rail, the global leader  
in fully integrated freight car systems  
for the heavy haul rail market.**



Amsted Rail has been an industry leader in freight railroading for more than 100 years. Our experience, dedication and efficiency in servicing today's demanding heavy haul operations is unequalled as we keep railcars rolling in some of the world's toughest railroad environments. To learn more, visit [www.amstedrail.com](http://www.amstedrail.com).